

TOLON

Laundry Solutions
in the Line of Orange



Washer Extractor TWE 20 - 40

OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Second drain valve for water recovery

STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- 4 compartment top panel dispenser :
2 for liquid and 2 for powder
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Plexi double glass protection against heat
- Accelerometer for perfect balancing

MODEL	UNIT	TWE 20	TWE 40
Dry load	kg	20	40
Performance	kg/h	30	60
Cycle time	min	40-45	40-45
DRUM			
Drum diameter	mm	700	900
Drum depth	mm	534	575
Drum volume	l	204	385
Wash speed	rpm	37	35
Extraction speed	rpm	960	870
G-Force		360	366
DOOR			
Door opening ø	mm	455	455
HEATING			
Electric	kW	18	24
Steam	bar	4	4
ELECTRIC			
Electric consumption*	kW/h	1,8	2,4
Motor	kW	3	5,5
STEAM			
Steam valve connection ø	DN-BSP	15-1/2"	15-1/2"
Steam pressure	kPa	200-600	200-600
Steam consumption	kg/cycle	10	20
AIR			
Air connection ø	mm	optional / 8	optional / 8
WATER			
Inlet valve connection ø	DN-BSP	2 x 20-3/4"	2 x 20-3/4"
Water inlet (detergent) ø	DN-BSP	-	-
Water pressure	kPa	200-400	200-400
Water flow	l/min	120	120
Water consumption*	cold	l/cycle	148
	hot	l/cycle	41
Drain valve connection ø (outer)	mm	76	76
Drain flow	l/min	230	230
PROGRAMMABLE CONTROL			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
DIMENSIONS			
Standard WxDxH	mm	977x1131x1465	1179x1401x1510
Packing WxDxH	mm	1100x1200x1565	1185x1450x1580
WEIGHT			
Net	kg	480	890
Gross	kg	495	905
SOUND LEVEL			
	db(A)	62-72	63-77

* Consumption figures based on ‚Eco 60°C‘ program (main wash, 2 rinses)