



TOLON

Laundry Solutions
in the Line of Orange



Washer Extractors TWE 60 - 110

OPTIONS

- Dual heating (electric & steam) selectable through the control (not on TWE 110)
- Forward tilting
- Extra inlet valve for soft water
- Pneumatic inlet valves for faster filling, standard on TWE 110
- Pneumatic steam valve on TWE60, standard on TWE 110
- Second drain valve for water recovery
- Weighing cells to measure amount of linen and reduce the water, energy and detergent consumption accordingly

STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid or powder detergent in 3 or 6 compartment frontal dispenser (available end 2017)
Now soap dispenser on side with 5 compartments.
- Standard equipped for automatic soap dosing
- Drum and tub, as well as the entire cabinet made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" (TWE60) or 4" (TWE110) drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing

MODEL	UNIT	TWE 60	TWE 110
Dry load	kg	60	110
Performance	kg/h	90	165
Cycle time	min	40-45	40-45
DRUM			
Drum diameter	mm	1100	1300
Drum depth	mm	610	830
Drum volume	l	579	1101
Wash speed	rpm	34	29
Extraction speed	rpm	770	720
G-Force	360	360	
DOOR			
Door opening ø	mm	550	675
HEATING			
Electric	kW	42	n/a
Steam	bar	4	4
ELECTRIC			
Electric consumption*	kW/h	4,2	n/a
Motor	kW	11	22
STEAM			
Steam valve connection ø	DN-BSP	25-1"	40-1½"
Steam pressure	kPa	200-600	200-600
Steam consumption	kg/cycle	28	50
AIR			
Air connection ø	mm	optional / 8	10
WATER			
Inlet valve connection ø	DN-BSP	2 x 25-1"	2 x 50-2"
Water inlet (detergent) ø	DN-BSP	1 x 25-1"	1 x 25-1"
Water pressure	kPa	200-400	200-400
Water flow	l/min	160	500
Water consumption*	cold l/cycle	434	764
	hot l/cycle	121	212
Drain valve connection ø (outer)	mm	76	114
Drain flow	l/min	230	600
PROGRAMMABLE CONTROL			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
DIMENSIONS			
Standard WxDxH	mm	1658x1580x1926	1858x1979x2074
Tilting WxDxH	mm	1805x1601x2170	1990x1995x2270
Packing WxDxH	mm	1700x1650x2076	1960x2250x2225
Packing Tilting WxDxH	mm	1900x1750x2277	2100x2300x2420
WEIGHT			
Net	kg	1850	4170
Gross	kg	1875	4220
SOUND LEVEL			
	db(A)	67-77	70-77

* Consumption figures based on ,Eco 60°C' program (main wash, 2 rinses)